

Telehandler / Zoom Boom

Used Telehandler Sacramento - Telehandlers go by many different names including a boom lift, telescopic handler, Cherry picker or teleporter. This industrial machine is commonly used in a variety of industries and in agriculture. This machine functions similarly to a crane and a forklift with the ability to extend upward and forward. Numerous attachments can be placed at the end of the articulating boom to conduct a variety of different jobs. Different attachments such as a bucket, pallet forks, a muck grab or a winch can help the machine complete many jobs. The pallet forks are the most popular telehandler attachment. Pallet forks enable the operator to move loads to and from a variety of locations that would otherwise be considered unreachable with a standard forklift. These machines enable cargo pallets to be unloaded and loaded from a trailer and placed on rooftops, racking or other high and hard to access locations. Typically, high locations would traditionally require a crane; however, telehandlers can facilitate these tasks easily and efficiently. It isn't always practical or affordable to rely on a crane or secondary machinery to complete the job. A bucket grab or a bucket is the most common attachments for telehandlers within the agricultural sector. Relocating items from hard to reach areas that cannot rely on a wheeled loader or a backhoe loader give telehandlers a significant advantage. For instance, these industrial machines can directly access a hopper or trailer with high sides; applications that would otherwise rely on a conveyor, loading ramp or similar equipment. Having one item to complete a variety of jobs saves time, money and storage space. Telehandlers commonly work alongside a crane jib. Many attachments can be used such as power booms, grain and dirt buckets and rotators. Three-point linkage and power take-off can be used with agricultural models to make this machine particularly capable. However, the main advantage of the telehandler is additionally its' largest limitation. The boom acts as a lever when it extends or raises with heavy loads. Even with rear counterweights, this machine may become unstable from time to time; decreasing the lift capacity when the distance between the center of the load and the front of the wheels or the working radius increases. When a telehandler functions as a single boom loader (as opposed to twin arms) and carrying a heavy load, there can be a potential for weakness even in the best designs. A 5000 lb. capacity telehandler could lift 400 lbs. safely while fully extended with a retracted boom in conjunction with a low boom angle. The same piece of equipment with a five thousand pound lift capacity and retracted boom may be capable as supporting up to ten thousand pounds once the boom is raised to seventy degrees. There is a load chart on these machines to determine which tasks can be safely executed by taking the weight, angle and boom height into account. Updated telehandler models have computers and sensors. When the telehandler limits have been surpassed, the operator is cut off and warned from supplying further control input. Front stabilizers that enhance the lifting capacity of the machine while stationary can make a huge difference. A stabilizing rotary joint between the upper and lower frames may be called a mobile crane that can use a bucket. There are many models of telehandlers differing in size, weight, boom designs and reach. Telehandlers that weigh 11,000 pounds or less fall into the compact category. A two-stage boom is a popular option for compact models whereas the three or four boom design is common for bigger machines. The compact model showcases a low pivot boom to allow better cab visibility for the operator while transporting loads. There are narrower and smaller dimensions offered with the compact telehandler. The reach capacity for compact units is between thirteen to twenty feet and these units offer a lift capacity from five to seven thousand pounds. The versatility of the compact telehandler makes it popular in a variety of applications. This machine can be utilized for carrying tools or as a pick and place unit. Compact units are ideal for cramped locations. It is common for contractors to use this machine during framing and for residential jobs where there are height restrictions. These units can be useful for accessing internal building locations. Compact telehandlers are commonly used in nurseries, landscaping, multi-story construction, building strip malls and garages, masonry, erecting steel and more. Farming and agri-business applications often rely on telehandlers to accomplish many tasks.

Telehandlers come with crab steering or two or four-wheel drive options. The unit can travel over longer ranges at higher speeds with two-wheel drive, making it ideal for moving throughout job sites. The 4-WD units are capable of having a tighter turning radius and can travel difficult terrain. Crab steering increases overall maneuvering and enables the front and back wheels to move 45 degrees to the left or the right. There are a variety of cab interior options available for compact telehandlers. On entry-level models, there is a rollover cage for added safety. Higher models come with a heater, a completely enclosed cab, defroster and windshield wiper. Operators enjoy spacious accommodation for ultimate comfort. Additional options including satellite radio, air conditioning, armrests, cup holders, suspension seats and tilt steering are available. Different high-flow auxiliary hydraulics and high-pressure hydraulics run the variety of attachments. These attachments increase the functions the machine is capable of. Compact machines conduct ground-engaging jobs. It is easy to enjoy the benefits of a mini excavator by adding a simple bucket attachment to the telehandler. There are popular attachments including brooms for sweeping, truss booms for extended reach, side-shifting and rotating fork carriages, heavy and light-duty buckets, augers for planting trees or digging holes and many items. Skid steer attachments are being manufactured for certain compact telehandler designs for even more versatility.